



HL-5500L Series

An innovative new lockset.

Hyundai Metal is well known worldwide
as a manufacturer of quality Door Locks.


Hyundai

- Just a turn of the inside lever in either direction retracts both the deadbolt and latch at the same time
- Top lock is heavy duty deadbolt with the bottom lock having a cylindrical body
- Inside escutcheon conceals mounting screws



HL-5500L(L) ENT PCR

Door Preparation



Type 5500L cutout × strike


W - Standard Front : 1" (25mm) × 2 1/4" (57mm)
Wide Front : 1 1/8" (29mm) × 2 1/4" (57mm)

Specifications

Applications	For offices, schools, hospitals, apartments, hotel/motel, retail and other public buildings
For Doors	1 3/8" to 1 3/4" (35mm to 45mm)
Backset	2 3/8" (60mm) standard. 2 3/4" (70mm) or Adjustable optional
Front	Brass, Bronze ; 2 1/4" × 1" standard. 2 1/4" × 1 1/8" optional
Strike	Brass or Bronze ; K203-G2(Anti-rattle) and IC Deadbolt standard Full-lip, K203-G2 optional. Consult factory for other sizes and configurations
Roses	Brass or Bronze
Hand	Right or Left hand must be specified for "Flair" design only
Latchbolt	Zinc, 7/16" throw standard. Brass, 7/16" throw optional
Deadbolt	Brass, 1" throw with concealed hardened steel bar
Keys	Three, Brass standard ("L", "R" levers, "Egg" knob) Two, Brass standard ("Flair" lever)
Cylinder Body	Zinc, Kwikset 5 pin standard ("L", "R" levers, "Egg" knob) Brass, Schlage 6 pin standard ("Flair" lever) All levers available with Weiser, Arrow, Lockwood C 4, Schlage optional
Cylinder Plug	Brass
Masterkeying	Can be masterkeyed or grand masterkeyed. Construction key system available
Finishes (US Code)	3, 4, 5A, 10, 10B, 11, 15, 15A, 19, 26, 26D
Split Finishes	Outside finish specified first. Front & Strike finished to match inside trim unless otherwise specified

Lever Designs


'L' lever



Lever : Zinc Cast
Rose : Brass

Complies with codes requiring lever to return to within 1/2" of door face
& 'L' lever is available with I/C optional


'R' lever



Lever : Solid Zinc Cast
Rose : Brass

Complies with codes requiring lever to return to within 1/2" of door face


'Flair' lever



Lever : Zinc Cast
Rose : Brass

Right or Left hand must be specified
Right hand furnished unless otherwise specified

'Egg' knob



Knob : Solid Zinc Cast
Rose : Brass


Latches

To order latchbolt separately, specify part No. x Finish


Backset	Descriptions (Square Corner standard)	Part Number		
		Deadlatch	Springlatch	Deadbolt latch
2 3/8" (60mm)	1 1/8" (29mm) × 2 1/4" (57mm)	ENT-WD / 60	PRI-WD / 60	DB-WD / 60
	1" (25mm) × 2 1/4" (57mm)	ENT-STD / 60	PRI-STD / 60	DB-STD / 60
2 3/4" (70mm)	1 1/8" (29mm) × 2 1/4" (57mm)	ENT-WD / 70	PRI-WD / 70	DB-WD / 70
	1" (25mm) × 2 1/4" (57mm)	ENT-STD / 70	PRI-STD / 70	DB-STD / 70
Adjustable (2 3/8" ↔ 2 3/4")	1 1/8" (29mm) × 2 1/4" (57mm)	ENT-WD / ADJ	PRI-WD / ADJ	DB-WD / ADJ
	1" (25mm) × 2 1/4" (57mm)	ENT-STD / ADJ	PRI-STD / ADJ	DB-STD / ADJ
Round Corner Latches optional				

Square Corner Latches


Springlatch



Deadlatch




Deadbolt latch




Round Corner Latches


Springlatch



Deadlatch




Deadbolt latch




Strikes


No.K203-G2(Anti-rattle) strike (standard)



No. IC Deadbolt strike (standard)



Exploded View Drawing



Finishes

HD CODE	DESCRIPTIONS	US CODE	BHMA
PB	Polished Brass	3	605
SB	Satin Brass	4	606
AB	Antique Brass	5A	610
SBZ	Satin Bronze	10	612
OBZ	Oxidized Bronze, Oil Rubbed	10B	613
AC	Antique Copper	11	616
SN	Satin Nickel Plated	15	619
AN	Antique Nickel Plated	15A	620
EB	Ebony Brass	19	622
PCR	Polished Chromium Plated	26	625
SCR	Satin Chromium Plated	26D	626



Zinc levers are plated to match BHMA finish.
Custom colors available, consult factory. (Specify quantity, functions and US finish.)

How To Order

Hyundai Line	HL
Model	5500L
Lever Type	L
Function	ENT
Finish	PCR
Backset	STD / 60
Q'ty	100

Sample :
HL- 5500L (L) ENT PCR STD/60 -100 sets

Functions

Outside	Inside	Type	ANSI	Function Description
		Entrance	HF 97	<ul style="list-style-type: none"> · Deadlocking latch bolt is operated by lever from either side except when outside lever is made rigid or free spinning by locking device inside. · When outside lever is locked, deadlocking latchbolt is operated by key outside. · Inside locking device is manually operated to unlock outside lever. · Rotating push button from inside or key from outside extends deadbolt to locked position. · Both deadbolt and deadlocking latchbolt are retracted by rotating inside lever. · Closing door shall not release locking device inside.
		Storeroom	HF 98	<ul style="list-style-type: none"> · Deadlocking latchbolt is operated by key outside or rotating inside lever. · Outside lever is always rigid. · Key outside projects or retracts deadbolt. · Rotating inside lever or key outside retracts deadbolt and deadlocking latch bolt.

※ Privacy, Passage, Classroom, functions are available on request

Button types

- Push Button standard
- Push & Turn Button, Universal Turn Button optional



株式會社 現代金屬
HYUNDAE METAL CO., LTD.

Main Factory :

#720, Daecheon-dong, Dalseo-gu, Daegu, Korea.

Tel No. : 82-53-586-9719, 82-53-589-9840~3

Fax No. : 82-53-587-5890

Http: // www.hyundaelock.com

E-mail : hyundaelock@hyundaelock.com